

Technical Data Sheet



STAR-SAFE BRAKE FLUID DOT-4 Brake & Clutch Fluid

PRODUCT INFORMATION

BRAKE FLUID DOT-4 is recommended for use in all vehicle braking systems, from motorcycles up to large trucks where a DOT 2, DOT 3 or DOT 4 type product is requested. It is manufactured from synthetic polyethylene glycol esters and Syntec® additives enabling it to withstand the extreme temperatures associated with hard driving in hot climates. It always exhibits constant reliable braking performance.

BRAKE FLUID DOT-4 is a high performance high temperature brake fluid designed to ensure constant performance in all braking systems. It is manufactured in Europe from premium quality synthetic base fluids and specially selected Syntec® additives. It exhibits superior performance in all vehicles, in all driving conditions. Brake systems should be flushed and re-filled every 2 years. Avoid extended exposure to air or moisture. Please ensure product specifications match vehicle requirements before use.

PERFORMANCE LEVEL

FMVSS No. 116 DOT-4,

SAE J1704,

ISO 4925 Class 4.

Technical Properties

Test	Method	Typical Values
Color	Clear and Bright	Clear and Bright
Density @ 15 °C*	ASTM D 4052	1,0797
Kinematic Viscosity (40°C)	ASTM D445 - [mm ² /s = cSt]	6,979
Kinematic Viscosity - 100°C	ASTM D445 - [mm ² /s = cSt]	1,994
Pour Point, °C	ASTM D97	<-57

Health & Safety Please refer to the relevant health & safety data sheet, a copy of which is freely available to all our customers

The specifications above are typical but, may be changed without notice, always consult owner's manual before use. Values are indicative of standard test values and may change in line with industry norms. No warrantee is expressed or implied.

Produced on behalf of Star Oil Ltd by Mactex Oil Distribution Ltd, Ireland.

www.staroil.com.gh