

# Technical Data Sheet

## PRO-TEC SYN 5W/40 SN/CF

### High Performance Synthetic Petrol & Diesel Engines

#### PRODUCT INFORMATION

Pro-Tec SYN 5W-40 FE delivers ultimate engine protection for all modern high-powered petrol and diesel vehicles with or without exhaust after-treatment systems (DPF, SCR). If you wish to enjoy trouble-free use of your prestige vehicle, then this is the oil for you. Especially suited to 4 x 4s and SUVs. Ultimate protection is assured in all driving conditions.

Pro-Tec SYN 5W-40 FE is a new generation synthetic motor oil designed for use in all modern Petrol and Diesel engines. It is specifically designed for use in the latest high-powered engines where reduced lubricant volumes require the oil work harder to protect the engine. This fuel-efficient lubricant offers the best in-class engine and exhaust emission system protection. Please ensure product specifications match vehicle requirements before use.

#### PERFORMANCE LEVEL

SAE 5W-40, API SN/CF, ACEA C2/C3\*, VW 504/507, 501.00/502.00/505.00  
 MB 229.1/ 229.3, 229.51/229.31, BMW II-04, Renault RN 0700/0710, GM Dexos 2.  
 Porsche C30, NISSAN, Toyota, Landrover, Jaguar, Ferrari, Infinity.

#### Technical Properties

Test	Method	Typical Values
Color	Clear and Bright	Clear and Bright
Density @ 15 °C*	ASTM D 4052	0,8785
Kinematic Viscosity (40°C)	ASTM D445 [mm <sup>2</sup> /s = cSt]	127,2
Kinematic Viscosity-(100c)	ASTM D445 [mm <sup>2</sup> /s = cSt]	15,79
Viscosity Index	ASTM D2270	131
Pour Point, °C	ASTM D97	-39

Health & Safety Please refer to the relevant health & safety data sheet, a copy of which is freely available to all our customers

The specifications above are typical but, may be changed without notice, always consult owner's manual before use. Values are indicative of standard test values and may change in line with industry norms. No warrantee is expressed or implied.

Produced on behalf of Star Oil Ltd by Mactex Oil Distribution Ltd, Ireland.