

# Technical Data Sheet



## STAR-TRANS ATF D-III G Automatic Transmission Fluid ATF 3

### PRODUCT INFORMATION

ATF D III-G is a premium quality synthetically enhanced ATF Fluid suitable for use in automatic transmissions on Cars, Vans, Buses and Trucks requiring a D-III G or older ATF fluid. This product is also suitable for use in automotive power steering systems (PSF). Smooth low noise gear change and longer operating life can be expected with this product. Reduces wear, noise and fuel consumption.

ATF-D III-G is manufactured in Europe from a blend of premium base oils and synthetic additives. ATF-DIII delivers smooth gear change, reduced transmission wear and longer life. Please ensure product specifications match vehicle requirements before use.

### PERFORMANCE LEVEL

Dexron III-G /IIIF/ IID, Mercon V, Honda ATF-2, Toyota WS. Borg Warner  
MB 236.7, 236.5, CAT TO-2, Allison C-4, MAN 339 V1, Z1.

### Technical Properties

Test	Method	Typical Values
Color	Clear and Bright	RED
Density @ 15 °C*	ASTM D 4052	0,8778
Kinematic Viscosity (40°C)	ASTM D445 - [mm <sup>2</sup> /s = cSt]	31,29
Kinematic Viscosity - 100°C	ASTM D445 - [mm <sup>2</sup> /s = cSt]	5,296
Viscosity Index	ASTM D2270	99
Flash Point, °C	ASTM D92	
Pour Point, °C	ASTM D97	-36

Health & Safety Please refer to the relevant health & safety data sheet, a copy of which is freely available to all our customers

The specifications above are typical but, may be changed without notice, always consult owner's manual before use. Values are indicative of standard test values and may change in line with industry norms. No warrantee is expressed or implied.

Produced on behalf of Star Oil Ltd by Mactex Oil Distribution Ltd, Ireland.

[www.staroil.com.gh](http://www.staroil.com.gh)